CATÁLOGOS TÉCNICOS - TECHNICAL CATALOGUES

Rev. 2025-06

BRIDAS NEUMÁTICAS - PNEUMATIC CLAMPS

Brida Neumática / Pneumatic Clamp — CPR25

Diam. 25mm
Clamp. 30Nm
Hold. 75Nm
Ang. 15-105°
Weight. 2,0Kg.

PDF Catalogue

Brida Neumática / Pneumatic Clamp — CPL40

Diam. 40mm
Clamp. 140Nm
Hold. 380Nm
Ang. 2-135°
Weight. 2,2-2,7Kg.

PDF Catalogue

Brida Neumática / Pneumatic Clamp — CPL50/63

EU Norm
Diam. 50/63mm
Clamp. 250/420Nm
Hold. 1.300/1.700Nm
Ang. 2,5-135°
Weight. 4,0/5,0Kg.

PDF Catalogue

Chiusura Pneumatica / Pneumatic Clamp — CPL80

EU Norm
Diam. 80mm
Clamp. 1.000Nm
Hold. 2.500Nm
Ang. 3-135°
Weight. 14,5Kg.

PDF Catalogue

Brida Neumática / Pneumatic Clamp — CPLV50/63

Toll.Comp.(V).
10mm/230mm
EU Norm
Diam. 50/63mm
Clamp. 200/280Nm
Hold. 200/280Nm
Ang. 2,5-135°
Weight. 4,0/5,0Kg.

PDF Catalogue

Brida Manuel / Manual Clamp — MC

HeavyDuty
SteelBody
Manual
Hold. 160Nm
Ang. 60-120°
Weight. 4,3Kg.

PDF Catalogue

Brida Neumática / Pneumatic Clamp — CPN50/63



Naams Norm
Diam. 50/63mm
Clamp. 250/420Nm
Hold. 1.300/1.700Nm
Ang. 2,5-135°
Weight. 4,0/5,0Kg.

PDF Catalogue

Chiusura Pneumatica / Pneumatic Clamp — CPN80

NAAMS Standard
Diam. 80mm
Clamp. 1.000Nm
Hold. 2.500Nm
Ang. 3-135°
Weight. 11,5Kg.

PDF Catalogue

Brida Neumática / Pneumatic Clamp — CPR50/63

HeavyDuty
SteelBody
Diam. 50/63mm
Clamp. 270/420Nm
Hold. 1.000
Ang. 15-120°
Weight. 5,0/5,5Kg.

PDF Catalogue

Brida Neumática / Pneumatic Clamp — DL63

HeavyDuty
SteelBody
Diam. 63mm
Clamp. 400Nm
Hold. 600Nm
Ang. 45-90°
Weight. 10,0Kg.

PDF Catalogue

PINZAS NEUMÁTICAS - PNEUMATIC GRIPPERS

Pinza Neumática / Pneumatic Gripper — B32A/B

Diam. 32mm
Clamp. 850N/250N
Ang. 22,5-160°
Weight. 1,3-1,5Kg.

PDF Catalogue

Pinza Neumática / Pneumatic Gripper — B40A/B B40VA/B

Diam. 40mm
TolleranceComp. (V)
Clamp. 1.400/600N
Clamp(V). 1.050/460N
Ang. 22,5-160°
Weight. 2,5Kg.

PDF Catalogue

Pinza Neumática / Pneumatic Gripper — G40.1

Diam. 40mm
Clamp. 130Nm
Hold. 200Nm
Ang. 15-105°
Weight. 1,8Kg.

PDF Catalogue

Pinza para Transfer / Transfer Gripper — G20

Diam. 22mm
Clamp. 20Nm
Hold. 50Nm
Ang. 15-90°
Weight. 0,8Kg.

PDF Catalogue

DISPOSITIVOS DE CENTRADO - LOCATOR DEVICES

Dispositivo de Centrado / Locator Device — DCP30.1

Diam. 30mm
Stroke. 20-40Nm
PushForce. 350N
PullForce. 250N
RadialForce. 70N
AxialTorque. 4Nm
Weight. 0,8-1,1Kg.

PDF Catalogue

Dispositivo de Centrado / Locator Device — DCP40

Diam. 40mm
Stroke. 20-60mm
PushForce. 600N
PullForce. 500N
RadialForce. 150N
AxialTorque. 4-6Nm
Weight. 1,7-2,0Kg.

PDF Catalogue

Dispositivo de Centrado / Locator Device — DCP63.1

Diam. 63mm
Stroke. 20-60mm
PushForce. 1500N
PullForce. 1400N
RadialForce. 200N
AxialTorque. 4-6Nm
Weight. 2,8-3,1Kg.

PDF Catalogue

Dispositivo de Centrado / Locator Device — DCP40 (CNOMO STANDARD)

CNOMO

Diam. 40mm
Stroke. 25-50mm
PushForce. 600N
PullForce. 500N
RadialForce. 150N
AxialTorque. 4-6Nm
Weight. 1,7-2,0Kg.

PDF Catalogue

Dispositivo de Centrado / Locator Device — DCPD40W

Diam. 40mm
Stroke. 20-40Nm
PushForce. 600N
PullForce. 500N
RadialForce. 80N
Ma. 6Nm
Mb. 3Nm
Weight. 1,1-1,2Kg.

PDF Catalogue

Dispositivo de Centrado / Locator Device — DCPD63.1

Diam. 63mm
Stroke. 20-60Nm
PushForce. 1500N
PullForce. 1350N
RadialForce. 200N
Ma. 60Nm
Mb. 30Nm
Weight. 3,6-3,8Kg.

PDF Catalogue

Dispositivo de Centrado / Locator Device — DCPD50U

Toggle Lock System
Diam. 50mm
Stroke. 40mm
PushForce. 1000N
PullForce. 800N
RadialForce. 400N
Ma/Mb 40/80Nm
Weight. 6,7-7,0Kg.

PDF Catalogue

Borrar la caché del navegador para asegurarse de descargar la última versión de los catálogos o de los 3D / Cancel your web browser cache in order to be sure to download the last release catalogues or 3D

BRIDAS DE UÑETA (PIN CLAMPS) - UNDERBODYCLAMPS

Brida Uñeta UnderbodyClamp — DCA50.2

SteelBody
Diam. 50mm
Clamp. 400dN
Hold. 470dN
HighStrengthPin
PinØ. 20-40mm
Weight. 5,7Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DCA50R.1



SteelBody
Diam. 50mm
Clamp. 250dN
Hold. 380dN
HighStrengthPin
PinØ. 18-40mm
Weight. 3,4Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DCA50Z.1

Horizontal LayOut
AluBody
Diam. 50mm
Clamp. 200dN
Hold. 330dN
HighStrengthPin
PinØ. 18-30mm
Weight. 3,0Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DCA40G

LightWeight
AluBody
Diam. 40mm
Clamp. 110dN
Hold. 200dN
HighStrengthPin
PinØ. 16-32mm
Weight. 1,8Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DCA63V.2/V6

NEW

Toll.Comp (V) 3mm
opz.(V6) 6mm
Diam. 63mm
Clamp. 220-280dN
Hold. 330dN
HighStrengthPin
PinØ. 20-40mm
Weight. 7,0Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DCA63LxV

90° Rotable Hook
Toll.Comp.(V). 3mm
Diam. 63mm
Clamp. 200-280dN
Hold. 330dN
HighStrengthPin
PinØ. 20-40mm
Weight. 7,0Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DCA63CV

SteelBody
Pin-Hole Gap Comp.
Toll.Comp.(V). 3mm
Diam. 63mm
Clamp. 220-280dN
Hold. 330dN
HighStrengthPin
Weight. 7,0Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DCA63.1

HeavyDuty
SteelBody
Diam. 63mm
Clamp. 700dN
Hold. 770dN
HighStrengthPin
PinØ. 20-40mm
Weight. 7,3Kg.

PDF Catalogue

Brida Uñeta UnderbodyClamp — DPA50

SteelBody
Diam. 50mm
Clamp. 400dN
Hold. 470dN
Weight. 6,2Kg.

PDF Catalogue

BASCULANTES - PIVOT UNITS

Basculantes Pivot Unit — RFM.2/RF.2

SBI Brake System
Hydraulic Control
Angles Changeable
D. 100-125-160-200
Ang. 15°-129°
190-800Nm (90°)

PDF Catalogue

Basculantes Pivot Unit — RCM.2/RC.2

Angles Changeable
Hydraulic Control
D. 100-125-160-200
Ang. 15°-129°
190-800Nm (90°)

PDF Catalogue

Basculantes Pivot Unit — RP80.2

Diam. 80
Flat Cylinder
Ang. 15-135°
100Nm (90°)

PDF Catalogue

Basculantes Electrico Electric Pivot Unit — GRE

ServoMotor 400V
ServoAxis
Controlled
Ang. 0-135°
Torque: 500Nm
Hold: 2.000Nm
3,5 Sec. 0°-->135°
Weight: 61Kg.

PDF Catalogue

Ribaltatore Elettrico Electric Pivot Unit — GRE-FESTO



ServoMotor 680V
ServoAxis
Controlled
Ang. 0-135°
Torque: 500Nm
Hold: 2.000Nm
3,2 Sec. 0°-->135°
Weight: 47Kg.

PDF Catalogue

MESAS LINEALES - LINEAR UNITS - (1/2)

Mesas Lineales Linear Unit — SLD.1

SBI Lock System
2 Work Positions
Stroke Changeable
D. 40-50-63-80-125
Stroke. 1-500mm
Payload. 40-600Kg.
Weight. 9,5-305 Kg.

PDF Catalogue

Mesas Lineales Linear Unit — SLDS.2

Clamps Lock System
2 Work Positions
Stroke Changeable
Diam. 63-80-125
Stroke. 1-500mm
Payload. 150-600Kg.
Weight. 54-285 Kg.

PDF Catalogue

Mesas Lineales Linear Unit — SLG40

LightWeigt
Pin Lock System
2 Work Positions
Stroke Changeable
Diam. 40
Stroke. 1-300 mm
Payload. 25 Kg.
Weight. 6,5-9,0 Kg.

PDF Catalogue

Mesas Lineales Linear Unit — SLCP63



Togle Lock System
1 Work Positions
Stroke Changeable
Diam. 63
Stroke. 5-90 mm
Payload. 15 Kg.
Weight. 8,0 Kg.

PDF Catalogue

MESAS LINEALES - LINEAR UNITS Continue (2 of 2) ----->

Borrar la caché del navegador para asegurarse de descargar la última versión de los catálogos o de los 3D / Cancel your web browser cache in order to be sure to download the last release catalogues or 3D

MESAS LINEALES - LINEAR UNITS - (2/2)

Mesas Lineales Servo
Servo Linear Unit
SLDE

Servo Unit
SBI Lock System
4 Work Positions
Stroke Changeable
Sizes. 63-80
Stroke. 0-500mm
Payload. 150-250Kg.

PDF Catalogue

Mesas Lineales Servo
Servo Linear Unit
SE80

ServoMotor 400V
ServoAxis
Controlled
Stroke 0-250mm
3,0 Sec. 0-250mm
Stroke 0-500mm
4,5 Sec. 0-500mm
Payload. 250Kg.

PDF Catalogue

Mesas Lineales Servo
Servo Linear Unit
SE 3D XYZ

Customized Linear
Systems 3D XYZ
ServoMotor
Controlled

Example:
Strokes 500mm
Payload. 200Kg.

Info

MOLTIPLICADORES DE FUERZA - FORCE MULTIPLIERS

Moltiplicador de Fuerza
Force Multipliers
FM100

SteelBody
Diam. 100mm
FwStroke. 50-200mm
PwStroke. 8mm
FW Force. 460daN
PW Force. 4.500daN
Weight. 20,5-26,5Kg.

PDF Catalogue

Borrar la caché del navegador para asegurarse de descargar la última versión de los catálogos o de los 3D / Cancel your web browser cache in order to be sure to download the last release catalogues or 3D